

FACESTOCK DESCRIPTION: 60# Recycled Vellum With 100% PCW

100% Recycled Vellum is the perfect "green" choice. This facestock uses the highest quality recycled fiber available to produce one of the brightest and whitest vellum facestocks made with 100% post-consumer fiber. It is excellent for high speed packaging lines and is a great stock for premium and eco-friendly labeling such as wine bottles, gourmet food, and beverages. This paper is also made Carbon Neutral Plus and Processed Chlorine Free (PCF). It is FSC® certified by the Rainforest Alliance,



Basis Weight (25 x 38 / 500), GSM	88.8
Caliper, Microns	125
Brightness, %	95
Opacity, %	90
Tear, MD / CD, g	50 / 58
Tensile, MD / CD, kg	12.7
Smoothness, Sheffield, units	250
pH	7.5
Recycled Content / PCW, %	100 / 100
Regulatory Compliances	FSC® Certified, FSC® is a voluntary program, and not legally required to be adhered to, Processed Chlorine Free, Green Seal Certified, Green-E Certified, Rainforest Alliance, REACH, RoHS, CONEG, California Proposition 65, ASTM F963 Child Toy Safety, Carbon Neutral Plus Certified

FSC® is a registered trademark of Forest Stewardship Council™

ADHESIVE DESCRIPTION: H-318

H-318 is the ideal choice for high end beverage and spirits, with improved resistance to moisture and humidity after bottling and at presentation to the consumer. H-318 is an aggressive, blended emulsion acrylic adhesive with the unique ability to combine special characteristics from different adhesives. H-318 was engineered to provide excellent high initial tack and quicker label adhesion onto glass while providing functional converting performance on an array of paper and film face stocks.

Type	Hybrid
Classification	Emulsion Acrylic
Minimum Application Temp., °C	-26
Service Temperature Range, °C	-29 to 79
Regulatory Compliances	FDA 21 CFR 175.105

LINER DESCRIPTION: 40# SC

A supercalendered bleached liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

Basis Weight (25 x 38 / 500), gsm	66
Caliper, microns	62.5
Brightness, %	78
Gloss, 75°, %	48
Opacity, %	65
Tear, MD / CD, g	32 / 34
Tensile, MD / CD, kg	15 / 9
Regulatory Compliances	ASTM F963 Child Toy Safety, CONEG, RoHS, REACH

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any



Wausau Coated Products, Inc.

Product Specification W032070
60# Recycled Vellum With 100% PCW / H-318 / 40# SC

product for their particular application . The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.